

Material Safety Data Sheet

Conforms to ISO11014-1:1994



Date of revised: 3/15/06

Date of printed: 01/05/07

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

<i>Product name</i> ARON ALPHA TYPE Remover AA-717	<i>Emergency Telephone Number</i> CHEMTREC (800) 424-9300 <i>Telephone Number for Information</i> (614) 879-9411
<i>Manufacture's Name</i> Krazy Glue Co., Div. of Toagosei America Inc.	
<i>Address</i> 1450 West Main Street West Jefferson, OH 43162	

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

Components (Specific Chemical Identity; Common Name(s) and CAS number)	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (Optional)
1 Acetone (CAS NO. 67-64-1)	750ppm 1800mg/m3 (TWA) 1000ppm	500ppm 1188mg/m3 (TWA) 750ppm		≥95
2 Cellulose 2-hydroxypropyl ether (CAS NO. 9004-64-2)	2400mg/m3 (STEL) Not Listed	1782mg/m3 (STEL) Not Listed		<3
3 Others	Not Listed	Not Listed		<2

SECTION 3 – HAZARDS IDENTIFICATION

3.1 Emergency Overview

Appearance and physical state = Clear Liquid
Odor = Mint-like

May be harmful if inhaled.
Causes eye irritation.

WARNING!
FLAMMABLE

HMIS Rating

HEALTH = 2
FLAMMABILITY = 3
REACTIVITY = 0

0-minimal, 1-slight, 2-moderate, 3-serious, 4-severe

3.2 Potential Health Effects

Immediate Hazards

INGESTION: Not expected to be swallowed under normal conditions of use. If accidentally swallowed, wash out mouth with water provided person is conscious. Might have harmful effects. Call a physician.

INHALATION: May be harmful if inhaled. Remove to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen.

SKIN: May cause irritation.

EYES: May cause irritation.

Delayed Hazards

Data not available

Note: None of the components present in this product at concentrations equal to or greater than 0.1% have been listed by NTP, classified by IARC, nor regulated by OSHA as a carcinogen.

SECTION 4 -FIRST AID MEASURES

INGESTION:

If accidentally swallowed, dilute by drinking large quantities of water. Immediately contact poison control center or hospital emergency room for any other additional treatment directions.

INHALATION:

If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Call a physician.

SKIN:

In case of skin contact, flush with copious amounts of water for at least 15 minutes. Remove contaminated clothing and shoes. Call a physician.

EYES:

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

SECTION 5 -FIRE FIGHTING MEASURES

Flash Point (Method Used) COMBUSTIBLE LIQUID
-18.0°C/-0.4°F (closed cap)

Flammable Limits (% by Vol.)

LEL	UEL
2.6%	12.8%

Extinguishing Media

Dry Chemical, carbon dioxide

Special Fire Fighting Procedures

Self-contained breathing apparatus with facepiece and protective clothing if involved in a fire of other materials

Unusual Fire and Explosion Hazards

None known

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEP TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED :

Eliminate all sources of ignition. Large quantities : Wipe and soak up material with absorbent like rags. Ventilate area. Material may be taken up on sand or clay absorbent. Small quantities : Soak up with absorbent material and remove to a chemical disposal area. Prevent entry into natural bodies of water.

Waste Disposal Method:

Immerse absorbent in a pail of water and dispose as oily rags.

SECTION 7 -HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING :

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing. Wash thoroughly after handling. Keep away from amines. Store in a cool, dry area away from sun and heat. Keep containers tightly closed. Exposure to small amounts of moisture, even in air, causes polymerization and renders the product unusable. Keep away from heat, sparks, flame and other ignition sources.

SECTION 8 -PERSONAL PROTECTION / EXPOSURE CONTROLS

8.1 Exposure Controls

ENGINEERING CONTROLS:

The following exposure control techniques may be used to effectively minimize employee exposure: local exhaust ventilation, enclosed system design, process isolation and remote control in combination with appropriate use of personal protective equipment and prudent work practices. These techniques may not necessarily address all issues pertaining to your operations. We, therefore, recommend that you consult with experts of your choice to determine whether or not your programs are adequate. If airborne contaminants are generated when the material is heated or handled, sufficient ventilation in volume and air flow patterns should be provided to keep air contaminant concentration levels below acceptable criteria.

8.2 Personal Protection

Where air contaminants can exceed acceptable criteria, use NIOSH/MSHA approved respiratory

protection equipment. Respirators should be selected based on the form and concentration of contaminants in air in accordance OSHA laws and regulations or other applicable standards or guidelines, including ANSI standards regarding respiratory protection. Use goggles if contact is likely. Wear impervious gloves as required to prevent skin contact.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (@ 1 atm) _____ 56°C or 133°F

Specific Gravity (H₂O = 1 @ 25°C) _____ 0.79

Vapor Pressure (mmHg @ 20°C) _____ 187
(Pa @20°C) _____ 24931

Vapor Density (AIR = 1) _____ 2.0

Melting Point _____ -94°C

Evaporation Rate (Butyl acetate = 1) _____ <1

Solubility in Water _____ Miscible (Acetone)

VOC content (g/L) _____ 0 (SCAQMD Method 316B)

Appearance and Odor _____ Clear Liquid
Mint-like

SECTION 10 - STABILITY AND REACTIVITY

Stability

Unstable:
Stable: **X**

Conditions to Avoid

Under normal conditions

Incompatibility

(Materials to Avoid)
Bases, oxidizing agents, reducing agents. Might react violently with phosphorous oxychloride

Hazardous Decomposition or Byproducts

CO, CO₂, nitrogen oxides

Hazardous Polymerization

May Occur:
Not Occur: **X**

Conditions to Avoid

Under normal conditions

SECTION 11 - TOXICOLOGICAL INFORMATION

Route(s) of Entry :

Inhalation?
Yes

Skin?
Yes

Ingestion?
Yes

Health Hazards *(Acute and Chronic)*

Skin: Rapid polymerization will occur on skin with heat. If a quantity is large, skin burn may happen.

Inhalation: High vapor concentration can induce nasal mucous, headaches, and giddiness

Eye: Irritation will occur slightly

Signs and Symptoms of Exposure

Prolonged or repeated exposure to skin causes defatting and dermatitis. CNS depression. Narcotic effect. Damage to the lungs.

Medical Conditions Generally Aggravated by Exposure

Skin: Wash material off the skin with plenty of water.

Inhalation: Nasal mucous, headache and giddiness in some individuals.

Eye: Irritation.

SECTION 12 - ECOLOGICAL INFORMATION

Not available

SECTION 13 - DISPOSAL INFORMATION

Contact a licensed professional waste disposal service to dispose of this material. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is flammable. Observe all federal, state, and local environmental regulations.

SECTION 14 – TRANSPORT INFORMATION

14.1 U.S. Department of Transportation (DOT)

The data provided in this section is for information only and may not be specific to your package size. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

Flammable liquid

14.2 Canadian Transportation of Dangerous Goods (TDG)

WHMIS Classification: this product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by the CPR.

SECTION 15 - REGULATORY INFORMATION

15.1 U.S. Federal Regulations

OSHA Hazard Communication Standard 29CFR1910.1200

This material is a "health hazard" and/or a "physical hazard" as determined when reviewed according to the requirements of the Occupational Safety and Health Administration 29

CFR Part 1910.1200 "Hazard Communication" Standard.

SARA Title III: Section 311/312

Fire hazard
Immediate health hazard

SARA Title III Section 313 and 40 CFR Part 372

This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and Subpart C-Supplier Notification Requirement of 40 CFR Part 372.
None required per SARA TITLE III SECTION 313.

TSCA Section 8(b) Inventory

All reportable chemical substances are listed on the TSCA Inventory.
We rely on certifications of compliance from our suppliers for chemical substances not manufactured by us.

15.2 Canadian Regulations

Workplace Hazardous Materials Information System (WHMIS)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR) and the MSDS contains all the information required by the CPR.

CLASS D, DIV 2B
CLASS B, DIV 3

Canadian Environmental Protection Act (CEPA)

All reportable chemical substances are listed on the Domestic Substances List (DSL) or otherwise comply with CEPA new substance notification requirements.

National Pollutant Release Inventory (NPRI)

This product contains the following chemical(s) subject to the reporting requirements of the Canadian Environmental Protection Act (CEPA) subsection 16(1), National Pollutant Release Inventory.

15.3 State and Local Regulations

California Proposition 65

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986:

This product contains the following substance(s) known to the state of California to cause cancer.

Benzene

This product contains the following substance(s) known to the state of California to cause reproductive harm.

Benzene

SECTION 16- OTHER INFORMATION

To the best of our knowledge, the information contained herein is accurate. However, neither Toagosei

America Ltd. nor any of its subsidiaries any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.